

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

The following Listing of Claims will replace all prior versions, and listings, of claims in the application.

**LISTING OF CLAIMS:**

1. (Previously Presented) A damper mechanism comprising:  
a first rotating member being axially movably and unrotatably attached to a piston;  
a second rotating member being configured to rotate relative to said first rotating member, said second rotating member being fixed to a hub and arranged on both axial sides of said first rotating member;

a pair of first elastic members, said first elastic members being aligned in a rotational direction to operate in series with each other in said rotational direction; and

a second elastic member being configured to operate in parallel with said pair of first elastic members in said rotational direction, said second elastic member being configured to be compressed in said rotational direction after said pair of first elastic members is compressed to a first angle due to relative rotation of said first rotating member and said second rotating member.

2. (Original) The damper mechanism according to claim 1, wherein said second elastic member and said pair of first elastic members are aligned in said rotational direction.

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

3. (Original) The damper mechanism according to claim 2, wherein a plurality of said pair of first elastic members is provided, and a plurality of said second elastic members is placed between said plurality of pairs of first elastic members in said rotational direction.

4. (Original) The damper mechanism according to claim 3, wherein said second elastic member is placed in a radial position to overlap with the radial position of said first elastic members.

5. (Original) The damper mechanism according to claim 4, wherein said second elastic member is placed in the same radial position as that of said first elastic members.

6. (Original) The damper mechanism according to claim 5, further comprising a supporting member arranged between one elastic member of said pair of first elastic members and the other elastic member of said pair of first elastic members in said rotational direction, said supporting member being configured to contact rotational ends of said pair of first elastic members.

7. (Original) The damper mechanism according to claim 2, wherein said second elastic member is placed in a radial position to overlaps with the radial position of said first elastic members.

8. (Original) The damper mechanism according to claim 7, wherein said second elastic member is placed in the same radial position as that of said first elastic members.

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

9. (Original) The damper mechanism according to claim 1, further comprising a supporting member arranged between one elastic member of said pair of first elastic members and the other elastic member of said pair of first elastic members in said rotational direction, said supporting member being configured to contact rotational ends of said pair of first elastic members.

10. (Previously Presented) The damper mechanism according to claim 1, further comprising a third elastic member being configured to operate in parallel with said pair of first elastic members and said second elastic member in said rotational direction, said third elastic member being configured to be compressed in said rotational direction after said pair of first elastic members is compressed to said first angle and said second elastic member is compressed to a second angle due to relative rotation of said first rotating member and said second rotating member.

11. (Original) The damper mechanism according to claim 10, further comprising a stopper mechanism that stops relative rotation of said first and second rotating member at a third angle.

12. (Original) The damper mechanism according to claim 11, wherein said second angle is larger than said first angle, and said third angle is larger than said second angle.

13. (Previously Presented) A damper disk assembly comprising:  
a first disk member having first and second supporting parts arranged in a rotational direction, said first disk member being axially movably and unrotatably attached to a piston;

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

a second disk member being arranged on both axial sides of said first disk member, said second disk member having first and second supporting areas corresponding to said first and second supporting parts respectively, and said second disk member being fixed to a hub;

a pair of first elastic members being arranged inside said first supporting part and first supporting area, said pair of elastic members being aligned in said rotational direction to operate in series with each other in said rotational direction; and

a second elastic member being arranged inside said second supporting part and said second supporting area, said second elastic member being configured to operate in parallel with said pair of first elastic members in said rotational direction after said first elastic members are compressed to a first angle due to relative rotation of said first and second disk members.

14. (Original) The damper disk assembly according to claim 13, wherein said second elastic member and said pair of first elastic members are aligned in said rotational direction.

15. (Original) The damper disk assembly according to claim 13, wherein a plurality of said pair of first elastic members is provided, and a plurality of said second elastic members is placed between said plurality of pairs of first elastic members in said rotational direction.

16. (Original) The damper disk assembly according to claim 15, wherein said second elastic member is placed in a radial position to overlap with the radial position of said first elastic members.

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

17. (Original) The damper disk assembly according to claim 16, wherein said second elastic member is placed in the same radial position as that of said first elastic members.

18. (Previously Presented) The damper disk assembly according to claim 13, further comprising a supporting member arranged between one elastic member of said pair of first elastic members and the other elastic member of said pair of first elastic members in said rotational direction, said supporting member being configured to contact rotational ends of said pair of first elastic members.

19. (Original) The damper disk assembly according to claim 13, wherein a first rotational direction gap of a certain angle is secured between a rotational direction end of said second supporting part on one rotational side and a rotational direction end of said second elastic member.

20. (Original) The damper disk assembly according to claim 19, further comprising a third elastic member being arranged in a third supporting part of said first disk member and a third supporting area of said second disk member, wherein a second rotational direction gap is secured between a rotational direction end of said third supporting area on one rotational side and a rotational direction end of said third elastic member.

21. (Previously Presented). A damper mechanism comprising:  
a first rotating member being axially movably and unrotatably attached to a piston;

Appl. No. 10/787,171  
Amendment dated November 1, 2006  
Reply to Office Action of August 2, 2006

a second rotating member being configured to rotate relative to said first rotating member;

a pair of first elastic members, said first elastic members being aligned in a rotational direction to operate in series with each other in said rotational direction; and

a second elastic member being configured to operate in parallel with said pair of first elastic members in said rotational direction, said second elastic member being configured to be compressed in said rotational direction after said pair of first elastic members is compressed to a first angle due to relative rotation of said first rotating member and said second rotating member.